



EPCOM S-Line

Powered by Hikvision

- H.264 & dual-stream video compression
- Full channel@WD1(PAL:960×576,NTSC:960×480) resolution real-time recording
- Simultaneous VGA and CVBS outputs
- Alarm for video loss, motion detection, tampering and abnormal signal
- Embedded WEB server for remote access
- Mobile view on 3G/Wifi enabled device (iPhone, Android)
- Support 1 SATA HDD and 2 UBS2.0 ports for easy backup

Model	S04	S08	S16
Video / Audio input			
Video compression	H.264		
Video input	4-ch	8-ch	16-ch
Video input interface	BNC (1.0 Vp-p, 75 Ω), PAL/NTSC self-adaptive		
Audio compression	G.711u		
Audio input	1-ch, RCA (2.0 Vp-p, 1 kΩ)		
Two-way audio input	1-ch, RCA (2.0 Vp-p, 1 kΩ) (using Audio In)		
Video / Audio output			
VGA output	1-ch, resolution: 1080P: 1920×1080/60Hz,SXGA: 1280×1024/60Hz,720P: 1280×720/60Hz,XGA: 1024×768/60Hz		
CVBS output	1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480		
Encoding resolution	WD1 / 4CIF / 2CIF / CIF / QCIF		
Frame rate	25 fps (P) / 30 fps (N)		
Video bit rate	32 Kbps ~ 3072 Kbps, or user defined (Max. 3072 Kbps)		
Audio output	1-ch, RCA (Linear, 600 Ω)		
Audio bit rate	64 Kbps		
Dual-stream	Support; Sub-stream: CIF / QCIF @ 25 fps (P) / 30 fps (N)		
Stream type	Video, Video & Audio		
Synchronous playback	4-ch	8-ch	16-ch
Hard disk			
SATA	1 SATA interface (Not Included)		
Capacity	Up to 4TB capacity		
External interface			
Network interface	1, RJ45 10M / 100M Ethernet interface		
USB interface	2 × USB 2.0		
General			
Power supply	12 VDC		
Consumption (without HDD or DVD-R/W)	≤ 5W	≤ 7W	≤ 9W
Working temperature	-10 °C ~ +55 °C		
Working humidity	10% ~ 90%		
Chassis	1U chassis		
Dimensions(W × D × H)	200 × 200 × 45 mm		285 × 210 × 45 mm
Weight (without HDD or DVD-R/W)	≤ 0.8 kg	≤ 1 kg	≤ 1.5 kg

Available models

S04-S08-S16

Rear Panel of S08



1. VIDEO IN
2. VIDEO OUT
3. VGA Interface
4. AUDIO IN, RCA Connector
5. AUDIO OUT, RCA Connector

6. LAN Network Interface
7. USB Interface
8. GND
9. 12 VDC