

**EPMD4XV2**

**3" HD Analog 4 in 1 IR PTZ camera**

**epcom**<sup>®</sup>  
Professional Video Surveillance Solutions



## **Application:**

Can be widely used in the need for a wide range of high-definition quality monitoring sites, the use of scenarios: warehouse, underground, parking, access, staircase, supermarkets, Internet cafes, etc.

## **Product Overview:**

- 2.0MP 1/2.8" Low illumination 307CMOS, 4X optical zoom;
- Precision worm gear driven, keen responsive, smoothly operation, the precision deviation less than 0.1 degree;
- Support lightning protection, surge protection and voltage transient protection;
- Protection Grade: IP66;
- Support coaxial control, the distance of video transmission up to 500 meters in theory;
- Metal plus plastic case, support AHD /TVI / CVI / CVBS 4 in 1 signal mode switch.

## **Feature:**

- 4PCS Infrared lights, effective IR distance up to 20m.
- 355°endless pan range and 0°- 90°tilt range no blind monitor area.
- Max. pan preset speed of 80°/s and max. tilt preset speed of 80°/s
- Pan control speed 0°~80°/s, tilt control speed 0°~80°/s
- Support 220 presets,
- Support Proportional zoom function, rotation speed can be adjusted automatically according to zoom multiple.

## Technical Parameters:

Model	EPMD4XV2		
PTZ	IR distance	20m	
	Pan range and speed	Pan 355°endless rotate, speed 0° ~ 80°/S	
	Tilt range and speed	0° ~ 90°, speed 0° ~ 80°/S	
	Preset	220x	
	line scan	support 1x AB line scan	
Zoom camera	Video parameter	Resolution	2.0 MP 1920(H)X1080(V)
		Sensor	1/2.8" 2.0M 307 CMOS
		Illumination	Color: 0.005Lux@F1.2 Black: <a href="#">0.001Lux@F1.2</a>
		S/N	≥50dB
	Lens Parameter	Optical zoom	4X, 2.8 mm ~ 12mm; F1.7-F3.0
		Angle view	113.9°(Near) ~34.1°(Far)
	function	White balance	auto/manual
		Exposure mode	auto/manual
		BLC	Support
		Gain control	Auto/manual
		Electronic shutter	AUTO/ 1/50(1/60) -1/50000sec
		DNR	2D/3D digital
		Focus mode	auto/manual
		Day-night mode	Support
		Video output	AHD,TVI,CVI,CVBS
Port	Video port		
	Power port		
Others	Consumption		
	Working temperature/Humidity		
	Protection grade		
	Protection Grade		

## Product Dimension:(unit:mm)

