

**WI-PS120GF-24V
16FE+4Combo Gigabit 24V
Ports PoE Switch
with 16-Port PoE Datasheet**




Highlights

- 16FE+4 Gigabit Combo SFP Ports with 16 PoE
- Supports PoE power up to 24W for each port
- Supports 24V Passive PoE compliant PDs
- Internal power adapter supply 300W
- LED indicators for LINK/ACT, Power, PoE Status, 100/1000Mbps
- 16K entry MAC address table with auto-learning and auto-aging



Typical Applications



WI-TEK 24V Passive PoE Switch



Description

What This Product Does

16FE+4Combo Gigabit Switch with 16-Port PoE provides the seamless network connection. It integrates 1000Mbps Gigabit Ethernet and 10/100Mbps Fast Ethernet network capabilities.

How This Product Works

16 Auto-Negotiation RJ45 ports (port-1 to port-16) of the switch support Power over Ethernet (PoE) function. These PoE ports can automatically detect and supply power with those Passive PoE compliant Powered Devices (PDs). In this situation, the electrical power is transmitted along with data in one single cable allowing you to expand your network where there are no power lines or outlets, where you wish to fix devices such as APs, IP Cameras or IP Phones, etc.

Easy To Use

WI-PS120GF is easy to install and use. It requires no configuration and installation. With outstanding performance and quality, the WI-PS120GF 16FE+4Combo Gigabit Switch with 16-Port PoE is a great selection for expanding your home or office network.

Specifications

HARDWARE FEATURES

<p>Interface</p>	<p>16 10/100M POE Ports 4 1000M RJ45 Ports 4 SFP Ports</p>
<p>Network Media</p>	<p>10 Base-T: Pair 2 Category 3 and above UTP/STP(≤100 m) 100Base-TX: Pair 2 Category 5 and above UTP/STP(≤100m) 1000Base-T: Pair 4 Category 5 and above UTP/STP(≤1 00m) 1000Base-SX:62.5μm/50μm MMF (2m~550m) 1000Base-LX:62.5μm/50 um MM (2m~550 m) or 10μm SMF (2m~5000m)</p>

HARDWARE FEATURES

Fan Quantity	Fanless
Power Consumption	300W (max. with PoE device connected)
External Power Supply	AC110-265V 50/60HZ
PoE Ports (RJ45)	PoE PIN: 4,5+ 7,8- PoE Ports: Port1- Port16 Power Supply: 300W
Exchange Capacity	11.2G
Mac Address Table	16K
Dimensions	Product Size: 440 mm*290 mm*45mm (L*W*H)

SOFTWARE FEATURES

Transmission Method	Store-And-Forward
Advanced Functions	Priority Function Mac Address Auto-Learning And Auto-Aging Store and forward

SOFTWARE FEATURES

	IEEE 802.3x flow control for Full-duplex Mode Backpressure for Half-duplex Mode
--	--

OTHERS

Certification	CE, FCC, RoHS
Package Contents	POE Switch Electric Line Guide Book/Warranty Card 2L Shape Mount+4 Shim
Environment	Working Temperature: 0°C~40°C Storage temperature : -40°C~70°C Working Humidity : 10%~90% RH non-condensing Storage Hum idity: 5%~90% RH non-condensing