

# 802.3af/at PoE Injector

Power where you need it

## Features

- Compatible with all current Open Mesh access points except the OM2P
- Delivers data & power to 802.3at/af PoE-compliant devices
- Extends power to unwired areas up to 328-ft./100m
- Gigabit Ethernet in and out ports for high-speed devices
- Disconnect, short-circuit and surge protection for reliable, secure connections
- Up to 30W of output power
- Mounts to walls or ceilings



## Specifications

ATPOE 802.3af/at PoE Injector	
Standards	802.3 10BaseT 802.3u 100BaseT 802.3ab Gigabit Ethernet 802.3at/af Power-over-Ethernet
Maximum output power	30W
Physical interface	1 gigabit data port, 1 gigabit data & power output port, 1 IEC-320 C6 AC Connector
LED	Power (green)
Mounting	Wall or ceiling
Input voltage	100 to 240VAC
Input current	0.8A Max for 100VAC
AC input frequency	47-63Hz
Power lines	Pin4, 5:54V, Pin7, 8:Return
Additional protection	Short-circuit, surge (over current/over voltage)
Operating temperature	32°F to 104°F (0°C to 40°C)
Storage temperature	-22°F to 176°F (-30°C to 80°C)
Operating humidity	5 to 90% or less
Storage humidity	5 to 90% or less
Dimensions	3.9" x 2.27" x 1.3"
Warranty	1 Year